# Datasheet

Article Number: 016248

7P/12, 24V Coil (ISO 3732 - Type S, ISO 1185 - Type N, ISO 3731 - Type S, ISO 1724 - Type N Typ S (supplementary), Typ N (normal))



| | |
|---|---|
| Categories | Coiled Cord , Accessories |
| Standards | ISO 3732 - Type S , ISO 1185 - Type N , ISO 3731 - Type S , ISO 1724 - Type N |
| Industries | Cars , Agriculture , Commercial vehicles |

## Electrical Details and Temperature Resistance

| | |
|---|---|
| Temperature resistance [in °C] | -40.0 - 100.0 |
| Voltage [in V] | 12 , 24 |

## Packaging and Order Details

| | |
|---|---|
| Packaging | without packaging |

## Material

| | |
|---|---|
| Cable color | black |
| Material of cable | PUR |

## Connectivity

| | |
|---|---|
| No. of connected plugs | 0 |
| No. of connected sockets | 0 |
| No. of poles | 07 |

## Norms and Standards

| | |
|---|---|
| Addition to standard | Typ N (normal) , Typ S (supplementary) |

## Measures and Dimensions

| | |
|---|---|
| Max. extension length [in m] | 4,20 |
| Max. working length [in m] | 2,70 |
| No. of coils | 41 |
| Outer coil diameter [in mm] | 50,00 |
| Stripping length [in mm] | 30,00 |
| Wire cross-sectional area | 6x 1.5mm² + 1x 2.5mm² |
| cable cross-sectional area [in mm] | 9,50 |