Datasheet

Article Number: 111057



7P/24V Socket (ISO 3731 - Type S)

| Voltage [in V]24Design FeaturesType of sealscrew capMaterialscrew capContact termination surfacestandard (CuZn)Cover insert colorwhiteCover materialreinforced compositeHousing colorwhiteHousing materialreinforced compositeContact terminationscrew contactContact terminationscrew contactDo of poles07 | | |
|---|---|----------------------|
| Industries Commercial vehicles Electrical Details and Temperture Resistance Voltage [in V] 24 Design Features Type of seal screw cap Material Contact termination surface Cover insert color white Housing color white Housing material reinforced composite Contact termination reinforced composite Housing material screw contact Contact termination screw contact Housing material screw contact No. of poles 07 | Categories | Socket |
| Electrical Details and Temperture Resistance Voltage [in V] 24 Design Features screw cap Type of seal screw cap Material contact termination surface Contact termination surface standard (CuZn) Cover nasert color white Cover material reinforced composite Housing color white Rousing material reinforced composite Contact termination screw contact No. of poles 07 Measures and Dimensions screw contact | Standards | ISO 3731 - Type S |
| Voltage [in V]24Design FeaturesType of sealscrew capMaterialScrew capContact termination surfacestandard (CuZn)Cover naterialwhiteCover materialreinforced compositeHousing colorwhiteHousing materialreinforced compositeConnectivityscrew contactContact terminationscrew contactNo. of poles07Measures and DimensionsScrew contact | Industries | Commercial vehicles |
| Design Features Type of seal screw cap Material Contact termination surface standard (CuZn) Cover insert color white Cover material reinforced composite Housing color white Connectivity reinforced composite Contact termination screw contact No. of poles 07 Measures and Dimensions Screw contact | Electrical Details and Temperature Resistance | |
| Type of seal screw cap Material Screw cap Contact termination surface standard (CuZn) Cover insert color white Cover material reinforced composite Housing color white Housing material reinforced composite Connectivity screw contact Contact termination screw contact No. of poles 07 Measures and Dimensions Screw contact | Voltage [in V] | 24 |
| MaterialContact termination surfacestandard (CuZn)Cover insert colorwhiteCover materialreinforced compositeHousing colorwhiteHousing materialreinforced compositeConnectivityscrew contactContact terminationscrew contactNo. of poles07Measures and DimensionsScrew contact | Design Features | |
| Contact termination surfacestandard (CuZn)Cover insert colorwhiteCover materialreinforced compositeHousing colorwhiteHousing materialreinforced compositeConnectivityContact terminationscrew contactNo. of poles07Measures and Dimensions | Type of seal | screw cap |
| Cover insert colorwhiteCover materialreinforced compositeHousing colorwhiteHousing materialreinforced compositeConnectivitycontact terminationNo. of poles07Measures and Dimensionscontact termination | Material | |
| Cover materialreinforced compositeHousing colorwhiteHousing materialreinforced compositeConnectivityscrew contactContact terminationscrew contactNo. of poles07Measures and DimensionsScrew contact | Contact termination surface | standard (CuZn) |
| Housing color white Housing material reinforced composite Connectivity screw contact No. of poles 07 | Cover insert color | white |
| Housing material reinforced composite Connectivity Screw contact No. of poles 07 | Cover material | reinforced composite |
| Connectivity Contact termination No. of poles 07 | Housing color | white |
| Contact termination screw contact No. of poles 07 | Housing material | reinforced composite |
| No. of poles 07 Measures and Dimensions | Connectivity | |
| Measures and Dimensions | Contact termination | screw contact |
| | No. of poles | 07 |
| | Measures and Dimensions | |

For cable diameter

9,20mm - 11,50mm

