
# Datasheet

Article Number: 151059

2P/6-24V(16A) (hand lamp-) Socket (ISO 4165)






| | |
|---|---|
| Additional description | Cover remains in open position. Insertion of plug releases the lock. Cover closes automatically when plug is removed. |
| Categories | Socket |
| Standards | ISO 4165 |
| Industries | Agriculture |

## Electrical Details and Temperature Resistance

| | |
|---|---|
| Rated current / permanent load [in A] | 16 |
| Voltage [in V] | 6-24 |

## Packaging and Order Details

| | |
|---|---|
| Included in delivery | hexagon nut (M18) |
| Packaging | without packaging |

## Design Features

| | |
|---|---|
| Design/Version | slotted |

## Miscellaneous

| | |
|---|---|
| Product supplement | (hand lamp-) |

## Material

| | |
|---|---|
| Cover material | reinforced composite |
| Cover version | with automatic latching |
| Housing color | black |
| Housing material | reinforced composite |

## Connectivity

| | |
|---|---|
| Contact termination | plug-in contact |
| Features of plug-in contacts | flat terminal |
| No. of poles | 02 |

## Norms and Standards

| | |
|---|---|
| Protection | IP 20 |

## Measures and Dimensions

| | |
|---|---|
| Size of plug-in contacts | 6.3mm |