Datasheet

Article Number: 151131 3P/6-24V(25A) Socket (DIN 9680)







| Categories | Socket |
|------------|-------------|
| Standards | DIN 9680 |
| Industries | Agriculture |

Electrical Details and Temperature Resistance

| Rated current / permanent load [in A] | 25 |
|---------------------------------------|------|
| Voltage [in V] | 6-24 |

Packaging and Order Details

| Included in delivery | cap nut |
|----------------------|-------------------|
| Packaging | without packaging |

Design Features

| Design/Version | with 2-bolt-flange |
|----------------|--------------------|
| Type of seal | screw cap |

Material

| Contact surface | nickel (Ni) |
|------------------|----------------------|
| Cover material | reinforced composite |
| Housing color | black |
| Housing material | reinforced composite |

Connectivity

| Cable outlet | PG16, cap nut |
|------------------------------|-----------------|
| Contact termination | plug-in contact |
| Contact version | contact sleeve |
| Features of plug-in contacts | flat terminal |
| No. of poles | 03 |

Norms and Standards

| Protection | IP 54 , IP X4 |
|------------|---------------|
|------------|---------------|

Measures and Dimensions

| For cable diameter 7,00mm - 9,00mm |
|------------------------------------|
|------------------------------------|

