Datasheet

Article Number: 151288 3P/6-24V(32A) Socket (DIN 9680)





| Categories | Socket |
|------------|-------------|
| Standards | DIN 9680 |
| Industries | Agriculture |

Electrical Details and Temperature Resistance

| Rated current / permanent load [in A] | 32 |
|---------------------------------------|------|
| Voltage [in V] | 6-24 |

Packaging and Order Details

| Packaging | PE bag |
|-----------|--------|
|-----------|--------|

Design Features

| Design/Version | with 2-bolt-flange |
|----------------|--------------------|
| Type of seal | screw cap |

Material

| Contact surface | silver (Ag) |
|------------------|----------------------|
| Cover material | reinforced composite |
| Housing color | black |
| Housing material | reinforced composite |

Connectivity

| Cable outlet | cap nut |
|---------------------|----------------|
| Contact termination | crimp contact |
| Contact version | contact sleeve |
| No. of poles | 03 |

Norms and Standards

| Protection | IP 54 . IP X4 | |
|------------|---------------|--|
| PIOLECTION | IP 34 . IP A4 | |

Measures and Dimensions

| Contact: for max. wire cross section [in mm²] | 6,00 |
|---|------------------|
| For cable diameter | 6,00mm - 10,00mm |

