

Article Number: 251201 2P/24V(168A) Plug (VG 96917)



| | |
|------------|------------------|
| Categories | Plug |
| Standards | VG 96917 |
| Industries | Defense vehicles |

Electrical Details and Temperature Resistance

| | |
|---------------------------------------|-----|
| Peak current / short-term load [in A] | 305 |
| Rated current / permanent load [in A] | 168 |
| Voltage [in V] | 24 |

Packaging and Order Details

| | |
|-----------|--------|
| Packaging | PE bag |
|-----------|--------|

Design Features

| | |
|--------------|--------------|
| Type of seal | sealing plug |
|--------------|--------------|

Material

| | |
|----------------------|----------------------|
| Contact insert color | black |
| Contact surface | nickel (Ni) |
| Housing color | yellow (RAL 1021) |
| Housing material | reinforced composite |

Connectivity

| | |
|---------------------|----------------------------------|
| Cable outlet | cap nut , dual cable outlet 180° |
| Contact termination | crimp contact , solder contact |
| Contact version | contact sleeve |
| No. of poles | 02 |
| No. of seal outlets | double |

Norms and Standards

| | |
|------------|-----------------------|
| Protection | IP 54 , IP X4 , IP X7 |
|------------|-----------------------|

Measures and Dimensions

| | |
|---|---------|
| Contact: for max. wire cross section [in mm²] | 50,00 |
| For cable diameter | 13,00mm |