
# Datasheet

Article Number: 251289

2P/24V(500A) Plug (STANAG 4074 / MIL-PRF-62122)





| | |
|---|---|
| Categories | Plug |
| Standards | STANAG 4074 / MIL-PRF-62122 |
| Industries | Defense vehicles |

## Default

| | |
|---|---|
| US Army Ordnance No. | 11682338 |

## Electrical Details and Temperature Resistance

| | |
|---|---|
| Peak current / short-term load [in A] | 1000 |
| Rated current / permanent load [in A] | 500 |
| Temperature resistance [in °C] | -55.0 - 100.0 |
| Voltage [in V] | 24 |

## Packaging and Order Details

| | |
|---|---|
| NATO stock No. | 5935-00-567-0128 |
| Packaging | without packaging |

## Design Features

| | |
|---|---|
| Design/Version | rubberized |

## Material

| | |
|---|---|
| Contact insert color | black |
| Contact surface | silver (Ag) |
| Cover material | rubber |
| Cover version | push-on cap |
| Housing color | bronze green (RAL 6031-F9) |
| Housing material | break-proof metal |

## Connectivity

| | |
|---|---|
| Contact version | contact pin |
| No. of poles | 02 |

## Measures and Dimensions

| | |
|---|---|
| Contact: for max. wire cross section [in mm²] | 70,00 |