

Article Number: 501109

7P/12V 100% waterproof «WeatherLock™» Socket (SAE J560
Primary, ABS)



Categories	Socket
Standards	SAE J560
Industries	Commercial vehicles
Brand	WeatherLock™

Electrical Details and Temperature Resistance

Temperature resistance [in °C]	-40.0 - 85.0
Voltage [in V]	12

Packaging and Order Details

Packaging	bulk packaging
-----------	----------------

Design Features

Design/Version	with reinforcement bushings
Special feature	blunt cut socket pigtail , crimped , fully assembled

Miscellaneous

Product supplement	100% waterproof
--------------------	-----------------

Material

Contact insert color	green
Contact surface	nickel (Ni)
Cover insert color	green
Cover material	reinforced composite
Housing color	black
Housing material	reinforced composite

Connectivity

Cable outlet	cable outlet 180° , corrugated tube NW17
Contact termination	crimp contact
Contact version	contact pin
No. of poles	07
Outlet open or closed	n.a.

Norms and Standards

Addition to standard	ABS , Primary
Protection	IP 54 , IP X7 , IP X9K

Measures and Dimensions

American Wire Gauge (AWG)	4x 12AWG + 2x 10AWG + 1x 8AWG
Cable length [in in]	16,50
Cable length [in m]	0,42
Wire cross-sectional area	4x 3mm ² + 2x 5mm ² + 1x 8mm ²