

Article Number: 611083

## 7P/24V Coil (ISO 3731 - Type S)



|            |                     |
|------------|---------------------|
| Categories | Coiled Cord         |
| Standards  | ISO 3731 - Type S   |
| Industries | Commercial vehicles |

### Electrical Details and Temperature Resistance

|                                |               |
|--------------------------------|---------------|
| Temperature resistance [in °C] | -40.0 - 125.0 |
| Voltage [in V]                 | 24            |

### Packaging and Order Details

|           |        |
|-----------|--------|
| Packaging | PE bag |
|-----------|--------|

### Design Features

|                 |                                    |
|-----------------|------------------------------------|
| Special feature | requirements similar to ISO 4141-4 |
|-----------------|------------------------------------|

### Material

|                      |                      |
|----------------------|----------------------|
| Cable color          | black                |
| Contact insert color | white                |
| Housing color        | white                |
| Housing material     | reinforced composite |
| Material of cable    | PUR                  |

### Connectivity

|                                   |        |
|-----------------------------------|--------|
| Cable outlet                      | molded |
| Mounting of cable and socket/plug | molded |
| No. of connected plugs            | 1      |
| No. of connected sockets          | 0      |
| No. of poles                      | 07     |

### Norms and Standards

|            |       |
|------------|-------|
| Protection | IP 44 |
|------------|-------|

### Measures and Dimensions

|                              |   |
|------------------------------|---|
| Max. extension length [in m] | 4,50  |
| Max. working length [in m]   | 4,00  |
| Outer coil diameter [in mm]  | 36,00   |
| Wire cross-sectional area    | 6x 1.0mm <sup>2</sup> + 1x 1.5mm <sup>2</sup> |
| Working length [in m]        | 3,00  |