Datasheet

Article Number: 611248 7P/24V Economy Coil (ISO 1185 - Type N)



Packaging without packaging Packaging without packaging Design Features Economy version Special feature Economy version Miscellaneous Economy Product supplement Economy Material Source Sourc			
Industries Commercial vehicles Electrical Details and Temperature Resistance Temperature resistance [in *C] 40.0 - 85.0 Votage [in V] 24 Packaging and Order Details Packaging Packaging and Order Details without packaging Packaging features Economy version Descipt Features Economy version Miscellaneous Economy version Product supplement Economy version Cable color black Contact insert color black Contact insert color black Contact insert color black Material of cable PUR Connectivity Silver-colored Material of cable PUR Connectivity 1 Cable outlet grommet No. of connected plugs 1 No. of connected sockets 0 No. of connected sockets 0 No. of connected sockets 1 Protection P44 Max.working length [inm] 35.00	Categories		
Electrical Details and Tempersture Resistance Temperature resistance [in °C] 40.0-85.0 Yotage [in Y] 24 Packaging and Order Details vithout packaging Packaging without packaging Packaging Features Economy version Special feature Economy version Miscellaneous Economy Product supplement Economy Cable color black Contact insert color black Housing color silver-colored Housing material preduct supplement Cable color black Contact insert color black Housing color silver-colored Housing color silver-colored metal Material of cable PUR Cable cotlet grommet No. of connected plugs 1 No. of connected plugs 1 No. of connected sockets 0 No. of connected plugs 1 No. of connected plugs 1 No. of connected plugs 1 No. of	Standards	ISO 1185 - Type N	
Temperature resistance [in *C] 40.0-85.0 Voltage [in V] 24 Packaging and Order Details Packaging without packaging Packaging Features Special feature Economy version Miscellaneous Product supplement Economy Cable color black Contact insert color black Housing color black Noterial preak-proof metal Contact insert color black Housing color preak-proof metal No. of connected plugs 1 No. of connected plugs 1 No. of connected plugs 1 No. of poles 07 Protection protection Protection protection Protection protection Max. working length [inm] 3,50	Industries	Commercial vehicles	
Temperature resistance [in *C] 40.0 - 85.0 Voltage [in V] 24 Packaging and Order Details Packaging without packaging Packaging Features Special feature Economy version Miscellaneous Product supplement Economy Cable color black Contact insert color black Housing color silver-colored Housing material preak-proof metal No. of connected plugs 1 No. of connected plugs 1 No. of connected plugs 1 No. of poles 1 Protection Pacaments Protection protection Protection protection Max.working length [inm] 3,50 Outer coli diameter [in mm] 35,00	Electrical Details and Temperature Resistance		
Votage [in V]24Packaging and Order DetailsPackagingwithout packagingPackagingwithout packagingDesign FeaturesEconomy versionSpecial featureEconomy versionMiscellaneousEconomyProduct supplementEconomyCable colorblackContact insert colorblackHousing colorsilver-coloredHousing colorBlackHousing colorBlackKontertialPURContact insert colorBlackHousing colorSilver-coloredHousing colorIncancent and			
Packaging and Order Details Packaging without packaging Packaging Features Economy version Special feature Economy version Miscellaneous Economy Product supplement Economy Atterial Economy Cable color black Contact insert color black Housing color silver-colored Housing material break-proof metal Naterial of cable PUR Cable coultet grommet No. of connected plugs 1 No. of connected sockets 0 Protection IP 44			
Packaging without packaging Packaging without packaging Design Features Economy version Special feature Economy version Miscellaneous Economy Product supplement Economy Cable color black Contact insert color black Housing color silver-colored Housing material break-proof metal Material of cable PUR Connectivity Immet No. of connected plugs 1 No. of connected sockets 0 No. of opoles 07 Protection IP44 Max. working length [in m] 3,50 Max. working length [in m] 3,500	voitage [in v]	24	
Design Features Economy version Special feature Economy version Miscellaneous Economy Product supplement Economy Atterial Economy Cable color black Contact insert color black Housing color esek-proof metal Material of cable PUR Connectivity Immet No. of connected plugs 1 No. of connected sockets 0 Protection Immet No. of connected sockets 0 Protection Pt44 Max. working length [in m] 3,50 Max. working length [in m] 3,500	Packaging and Order Details		
Special feature Economy version Miscellaneous Economy Product supplement Economy Material Economy Cable color black Contact insert color black Housing color black-proof metal Housing material break-proof metal Material of cable PUR Connected plugs 1 No. of connected plugs 0 No. of connected plugs 0 No. of poles 0 Protection IP44 Max.working length [in m] 5,50	Packaging	without packaging	
Special feature Economy version Miscellaneous Economy Product supplement Economy Material Economy Cable color black Contact insert color black Housing color black-proof metal Housing material break-proof metal Material of cable PUR Connected plugs 1 No. of connected plugs 0 No. of connected plugs 0 No. of poles 0 Protection IP44 Max.working length [in m] 5,50			
Miscellaneous Economy Product supplement Economy Material Seconomy Cable color black Contact insert color black Housing color silver-colored Housing material break-proof metal Material of cable PUR Connectivity grommet Cable outlet grommet No. of connected plugs 1 No. of connected sockets 0 No. of poles 07 Not of poles IP44 Measures and Dimensions Signo Max.working length [in m] 3,50 Outer coil diameter [in mm] Signo	Design Features		
Product supplement Economy Material Economy Cable color black Contact insert color black Housing color silver-colored Housing material break-proof metal Material of cable PUR Connectivity grommet Cable outlet grommet No. of connected plugs 1 No. of connected sockets 0 No. of poles 07 Norms and Standards Fraction Protection IP 44 Max.working length [in m] 3,50 Outer coil diameter [in mm] 35,00	Special feature	Economy version	
Product supplement Economy Material Economy Cable color black Contact insert color black Housing color silver-colored Housing material break-proof metal Material of cable PUR Connectivity grommet Cable outlet grommet No. of connected plugs 1 No. of connected sockets 0 No. of poles 07 Norms and Standards Fraction Protection IP 44 Max.working length [in m] 3,50 Outer coil diameter [in mm] 35,00			
Material black Coble color black Contact insert color black Housing color silver-colored Housing material break-proof metal Material of cable PUR Connectivity grommet Colorenceted plugs 1 No. of connected sockets 0 No. of poles 07 Protection IP 44 Max.working length [in m] 3,50 Max.working length [in m] 3,50	Miscellaneous		
Material black Coble color black Contact insert color black Housing color silver-colored Housing material break-proof metal Material of cable PUR Connectivity grommet Colored plugs 1 No. of connected plugs 0 No. of connected sockets 0 No. of poles 07 Protection IP 44 Max.working length [in m] 3,50 Max.working length [in m] 3,50	Product supplement	Economy	
Cable colorblackContact insert colorblackHousing colorsilver-coloredHousing materialbreak-proof metalMaterial of cablePURConnectivitygrommetCable outletgrommetNo. of connected plugs1No. of connected sockets0No. of poles7ProtectionIP44Max.working length [in m]3,50Max.working length [in mm]3,500			
Contact insert colorblackHousing colorsilver-coloredHousing materialbreak-proof metalMaterial of cablePURConnectivitygrommetCable outletgrommetNo. of connected plugs1No. of connected sockets0No. of poles07ProtectionIP44Measures and DimensionsJacaMax. working length [in m]3,50Outer coil diameter [in mm]5,00	Material		
Housing colorsilver-coloredHousing materialbreak-proof metalMaterial of cablePURConnectivitygrommetCable outletgrommetNo. of connected plugs1No. of connected sockets0No. of poles07ProtectionIP44Max. working length [in m]3,50Otter coil diameter [in mm]3,500	Cable color	black	
Housing materialbreak-proof metalMaterial of cablePURConnectivityconnected plugsCable outletgrommetNo. of connected plugs1No. of connected plugs0No. of poles07Norms and Standardsrestored sourcesProtectionIP 44Max. working length [in m]3,50Outer coil diameter [in mm]35,00	Contact insert color	black	
Material of cablePURConnectivityConnectivityCable outletgrommetNo. of connected plugs1No. of connected sockets0No. of poles07Norms and StandardsIP 44Measures and Dimensions3,50Max. working length [in m]3,500	Housing color	silver-colored	
ConnectivityCable outletgrommetNo. of connected plugs1No. of connected sockets0No. of poles07Norms and StandardsIP 44ProtectionIP 44Max. working length [in m]3,50Outer coil diameter [in mm]35,00	Housing material	break-proof metal	
Cable outletgrommetNo. of connected plugs1No. of connected sockets0No. of poles07Norms and StandardsIP 44ProtectionIP 44Max.working length [in m]3,50Outer coil diameter [in mm]35,00	Material of cable	PUR	
No. of connected plugs 1 No. of connected sockets 0 No. of poles 07 Norms and Standards Protection IP 44 Max. working length [in m] 3,50 Outer coil diameter [in mm] 35,00	Connectivity		
No. of connected sockets 0 No. of poles 07 Norms and Standards 1944 Protection IP 44 Max. working length [in m] 3,50 Outer coil diameter [in mm] 35,00	Cable outlet	grommet	
No. of poles 07 Norms and Standards IP 44 Protection IP 44 Max. working length [in m] 3,50 Outer coil diameter [in mm] 35,00	No. of connected plugs	1	
Norms and Standards IP 44 Protection IP 44 Measures and Dimensions IP 44 Max. working length [in m] 3,50 Outer coil diameter [in mm] 35,00	No. of connected sockets	0	
Protection IP 44 Measures and Dimensions 3,50 Max. working length [in m] 3,50 Outer coil diameter [in mm] 35,00	No. of poles	07	
Protection IP 44 Measures and Dimensions 3,50 Max. working length [in m] 3,50 Outer coil diameter [in mm] 35,00			
Max. working length [in m] 3,50 Outer coil diameter [in mm] 35,00	Norms and Standards		
Max. working length [in m]3,50Outer coil diameter [in mm]35,00	Protection	IP 44	
Outer coil diameter [in mm] 35,00	Measures and Dimensions		
Outer coil diameter [in mm] 35,00	Max working length [in m]	3.50	

