# Datasheet

Article Number: 641338 7P/12V Coil (ISO 7638-2 ABS, EBS, ADR)



| | |
|---|---|
| Categories | Coiled Cord |
| Standards | ISO 7638-2 |
| Industries | Commercial vehicles |

## Electrical Details and Temperature Resistance

| | |
|---|---|
| Voltage [in V] | 12 |

## Packaging and Order Details

| | |
|---|---|
| Packaging | PE bag |

## Design Features

| | |
|---|---|
| Special feature | requirements similar to ISO 4141-4 |
| Type of seal | bending protection grommet |

## Material

| | |
|---|---|
| Cable color | black |
| Cover insert color | red |
| Housing color | black |
| Housing material | reinforced composite |
| Material of cable | PUR |

## Connectivity

| | |
|---|---|
| Cable outlet | bending protection grommet |
| No. of connected plugs | 1 |
| No. of connected sockets | 0 |
| No. of poles | 07 |

## Norms and Standards

| | |
|---|---|
| Addition to standard | ABS , ADR , EBS |
| Protection | IP 54 |

## Measures and Dimensions

| | |
|---|---|
| Max. extension length [in m] | 4,50 |
| Max. working length [in m] | 4,00 |
| Outer coil diameter [in mm] | 50,00 |
| Wire cross-sectional area | 5x 1.5mm² + 2x 4.0mm² |
| Working length [in m] | 3,00 |