Datasheet

Article Number: 251295 1P/12V(100A) Plug (SAE J560, SAE J3082)



	for liftgate operation and battery charging
Categories	Plug
Standards	SAE J560 , SAE J3082
Industries	Commercial vehicles
electrical Details and Temp	perature Resistance
Peak current / short-term load [in A]	160
Rated current / permanent load [in A]	100
Temperature resistance [in °C]	-40.0 - 85.0
Voltage [in V]	12
Packaging and Order Detail	s
Packaging	PE bag
Design Features	
-	
Design/Version	metal
Special feature	with external ground
Strain relief	stainless steel spring
Material	
Material Contact insert color	black
	black brass alloy
Contact insert color	
Contact insert color Contact material	brass alloy
Contact insert color Contact material Contact surface	brass alloy brass alloy
Contact insert color Contact material Contact surface Housing color	brass alloy brass alloy silver-colored
Contact insert color Contact material Contact surface Housing color Housing material	brass alloy brass alloy silver-colored
Contact insert color Contact material Contact surface Housing color Housing material	brass alloy brass alloy silver-colored zinc
Contact insert color Contact material Contact surface Housing color Housing material Connectivity Cable outlet	brass alloy brass alloy silver-colored zinc pull relief
Contact insert color Contact material Contact surface Housing color Housing material Connectivity Cable outlet Contact termination	brass alloy brass alloy silver-colored zinc pull relief screw contact



