Datasheet

Article Number: 611039



9 7P/24V Coil (ISO 3731 - Type S)

| Categories | Coil |
|---|---|
| Standards | ISO 3731 - Type S |
| Industries | Commercial vehicles |
| | |
| Electrical Details and Temperature Resistance | |
| Temperature resistance [in °C] | -40.0 - 100.0 |
| Voltage [in V] | 24 |
| | |
| Packaging and Order Details | |
| Packaging | PE bag |
| Design Fastures | |
| Design Features | |
| Type of seal | bending protection grommet |
| | |
| Material | |
| Cable color | black |
| Contact insert color | white |
| Housing color | silver-colored |
| Housing material | break-proof metal |
| Material of cable | TPE |
| Connectivity | |
| - | |
| Cable outlet | bending protection grommet |
| No. of connected plugs | 2 |
| No. of connected sockets | 0 |
| No. of poles | 07 |
| Norms and Standards | |
| Protection | IP 44 |
| | |
| Measures and Dimensions | |
| Max. extension length [in m] | 4,50 |
| Max. working length [in m] | 4,00 |
| Outer coil diameter [in mm] | 50,00 |
| Wire cross-sectional area | 6x 1.0mm ² + 1x 1.5mm ² |
| Working length [in m] | 3,00 |
| | |

