# Datasheet

Article Number: 611255

7P/24V Coil (ISO 3731 - Type S)



| | |
|---|---|
| Categories | Coil |
| Standards | ISO 3731 - Type S |
| Industries | Commercial vehicles |

## Electrical Details and Temperature Resistance

| | |
|---|---|
| Temperature resistance [in °C] | -40.0 - 125.0 |
| Voltage [in V] | 24 |

## Packaging and Order Details

| | |
|---|---|
| Packaging | retail bag |

## Design Features

| | |
|---|---|
| Special feature | requirements similar to ISO 4141-4 |

## Material

| | |
|---|---|
| Cable color | black |
| Contact insert color | white |
| Housing color | white |
| Housing material | reinforced composite |
| Material of cable | PUR |

## Connectivity

| | |
|---|---|
| Cable outlet | molded |
| Mounting of cable and socket/plug | molded |
| No. of connected plugs | 2 |
| No. of connected sockets | 0 |
| No. of poles | 07 |

## Norms and Standards

| | |
|---|---|
| Protection | IP 44 |

## Measures and Dimensions

| | |
|---|---|
| Max. extension length [in m] | 4,50 |
| Max. working length [in m] | 3,00 |
| Outer coil diameter [in mm] | 35,00 |
| Wire cross-sectional area | 6x 1.0mm² + 1x 1.5mm² |