


Article Number: 641167

15P/24V Coil (ISO 12098 ADR)



|            |                     |
|------------|---------------------|
| Categories | Coil                |
| Standards  | ISO 12098           |
| Industries | Commercial vehicles |

### Electrical Details and Temperature Resistance

|                |    |
|----------------|----|
| Voltage [in V] | 24 |
|----------------|----|

### Packaging and Order Details

|           |        |
|-----------|--------|
| Packaging | PE bag |
|-----------|--------|

### Design Features

|                 |                                    |
|-----------------|------------------------------------|
| Special feature | requirements similar to ISO 4141-4 |
| Type of seal    | bending protection grommet         |

### Material

|                    |                      |
|--------------------|----------------------|
| Cable color        | black                |
| Cover insert color | red                  |
| Housing color      | black                |
| Housing material   | reinforced composite |
| Material of cable  | PUR                  |

### Connectivity

|                          |                            |
|--------------------------|----------------------------|
| Cable outlet             | bending protection grommet |
| No. of connected plugs   | 2                          |
| No. of connected sockets | 0                          |
| No. of poles             | 15                         |

### Norms and Standards

|                      |       |
|----------------------|-------|
| Addition to standard | ADR   |
| Protection           | IP 54 |

### Measures and Dimensions

|                              |  |
|------------------------------|--|
| Max. extension length [in m] | 4,50   |
| Max. working length [in m]   | 4,00   |
| Outer coil diameter [in mm]  | 50,00  |
| Wire cross-sectional area    | 12x 1.5mm <sup>2</sup> + 3x 2.5mm <sup>2</sup> |
| Working length [in m]        | 3,00   |