


Article Number: 251095

2P/24V(135A) 插头 (VG 96917 E001B)



|            |                  |
|------------|------------------|
| Categories | Plug             |
| Standards  | VG 96917         |
| Industries | Defense vehicles |

## 电气细节和耐温性

|                                       |     |
|---------------------------------------|-----|
| Peak current / short-term load [in A] | 245 |
| Rated current / permanent load [in A] | 135 |
| Voltage [in V]                        | 24  |

## 包装和订单详情

|           |     |
|-----------|-----|
| Packaging | PE袋 |
|-----------|-----|

## 设计特点

|                 |              |
|-----------------|--------------|
| Design/Version  | 喷油           |
| Special feature | 配橡胶包胶金属环(黑色) |
| Type of seal    | 密封塞          |

## 材料

|                      |                   |
|----------------------|-------------------|
| Contact insert color | black             |
| Contact surface      | 银 (Ag)            |
| Housing color        | black             |
| Housing material     | break-proof metal |

## 连接

|                     |                                  |
|---------------------|----------------------------------|
| Cable outlet        | cap nut , dual cable outlet 180° |
| Contact termination | crimp contact , 焊接接触             |
| Contact version     | contact pin                      |
| No. of poles        | 02                               |
| No. of seal outlets | double                           |

## 规范和标准

|                      |                       |
|----------------------|-----------------------|
| Addition to standard | E001B                 |
| Protection           | IP 54 , IP X4 , IP X7 |

## 措施和尺寸

|                                               |         |
|-----------------------------------------------|---------|
| Contact: for max. wire cross section [in mm²] | 35,00   |
| For cable diameter                            | 12,00mm |